



Mielec 22.07.2020

STANDARD DIMENSIONAL TOLERANCES ON JOONGPOL PRODUCTS

Taking into account the production technology, the following standard tolerances are established on the products. These tolerances can be tightened in case of special customer requirements. If a client has special requirements for a product, we approach it individually and set tolerances for a specific product individually, making any necessary changes in the manufacturing technology.

PE / PE+HDPE / PE+PETM:

DENSITY: $\pm 10\%$

THICKNESS [mm]	4,0	6,0	8,0	10,0	12,0
TOLERANCE [mm]	$\pm 0,4$	$\pm 0,6$	$\pm 0,8$	$\pm 1,0$	$\pm 1,2$

WIDTH [mm]	500 – 620
TOLERANCE [mm]	± 10

LENGTH [mm]	1800 – 2000
TOLERANCE [m]	-10 / +30

XPE / XPE+HDPE / XPE+PETM:

DENSITY: $\pm 10\%$

THICKNESS [mm]	4,0	6,0	8,0	10,0	12,0
TOLERANCE [mm]	$\pm 0,4$	$\pm 0,5$	$\pm 0,6$	$\pm 0,6$	$\pm 1,0$

WIDTH [mm]	500 – 620
TOLERANCE [mm]	± 10

LENGTH [mm]	1800 – 2000
TOLERANCE [mm]	-10 / +30